



AWNING

Some of our units are equipped with a patio awning. Most will operate according to these instructions but there may be some variations. Your check-out agent covered the actual awning on your unit and this will serve only as a reminder for what you were shown.

Follow these steps to put the awning out:

- 1.) Release the travel locks on the awning support arms. They are located toward the upper portion of each support arm.
- 2.) Locate the awning rod. Use the rod to unlock the spring mechanism on the awning. It is generally located on the end of the awning that is near the front of the coach. It will be a small lever at the end of the awning tube. Pull the lever down to unlock the awning.
- 3.) Loosen the hold down knobs on the tension rafters at each end of the awning. They're located halfway up each support arm on the coach side of the arms.
- 4.) Use the awning rod to unfurl the awning. There should be a strap loop in the middle of the awning tube. Place the hooked end of the awning rod in this loop and pull toward you until the awning is out as far as it will go.
- 5.) Slide the tension rafter on each support arm out until the awning canvas is tight and tighten the knobs.
- 6.) Move to one of the support arms and locate the lever on the side of the arm. Pull out on the lever while sliding the arm out and away from the coach. Slide the arm out to the desired height and release the lever making certain it locks into place.
- 7.) Move to the other support arm and repeat the steps described in Step 4.

To lower the awning simply reverse the above procedures.

IMPORTANT NOTES:

- 1.) Stow the awning when it's raining. Water can accumulate and cause the awning to collapse.**
- 2.) Stow the awning when it's windy. High winds can damage the awning.**
- 3.) Stow the awning properly for travel. Check the travel locks frequently. An improperly stowed awning can unfurl while driving causing damage to the awning and endangering lives and property. It is your responsibility to check the travel locks before proceeding on your way.**
- 4.) You are responsible for the awning until the unit has been properly checked in by one of our agents. Avoid damage charges by properly using and stowing the awning.**
- 5.) Be extremely careful around trees. Tree branches rubbing against the stowed awning can damage the material and mechanisms.**